




TECHNICAL PROPERTIES



EN388



3442C

EN407



41XXXX

A: ABRASION (1-4)
B: CUT (1-5)
C: TEAR (1-4)
D: PUNCTURE (1-4)
F: ISO CUT (A-F)
P: IMPACT PROTECTION

ISO (A-F)
A | > 2 N
B | ≥ 5 N
C | ≥ 10 N
D | ≥ 15 N
E | > 22 N
F | > 30 N




ART.NO: 13-3HNFR
60 pairs (5 dozen)/Carton

CE
CAT II

7	8	9	10	11
XS	S	M	L	XL



TEKNISKA EGENSKAPER



EN388



3442C

EN407



41XXXX

A: NÖTNINGSMOTSTÅND (1-4)
B: SKÄRMOTSTÅND (1-5)
C: RIVHÅLLFASTHET (1-4)
D: PUNKTERINGSMOTSTÅND (1-4)
E: ISO SKÄRBESTÄNDIGHET (A-F)
F: SLAGSKYDD (P=godkänd)

ISO (A-F)
A | > 2 N
B | ≥ 5 N
C | ≥ 10 N
D | ≥ 15 N
E | > 22 N
F | > 30 N




Art.nr: 13-3HNFR
60 par (5 dussin)/Kartong

CE
CAT II

7	8	9	10	11
XS	S	M	L	XL



TECHNISCHE EIGENSCHAFTEN



EN388



3442C

EN407



41XXXX

A: ABRIEBFESTIGKEIT (1-4)
B: SCHNITTFESTIGKEIT (1-5)
C: WEITERREISSFESTIGKEIT (1-4)
D: DURCHSTICHFESTIGKEIT (1-4)
F: ISO SCHNITTFESTIGKEIT (A-F)
P: SCHLAGSCHUTZ (P=pass)

ISO (A-F)
A | > 2 N
B | ≥ 5 N
C | ≥ 10 N
D | ≥ 15 N
E | > 22 N
F | > 30 N



Art.nr: 13-3HNFR
60 paar (5 dutzend)/Karton

CE
CAT II

7	8	9	10	11
XS	S	M	L	XL




PROPRIETÀ TECNICHE

Abrasione



Taglio



Lacerazione



Urto



Ago



Foratura



Calore



Scariche elettriche



Resistenza all'acqua e agli oli



Grip



Respirazione



EN388



3442C



41XXXX

CAT II

A: RESISTENZA ALL'ABRASIONE (1-4)
B: RESISTENZA AL TAGLIO (1-5)
C: RESISTENZA ALLO STRAPPO (1-4)
D: RESISTENZA ALLA PERFORAZIONE (1-4)
F: ISO RESISTENZA AL TAGLIO (A-F)
P: IMPATTO (P=pass)

ISO (A-F)
A | > 2 N
B | ≥ 5 N
C | ≥ 10 N
D | ≥ 15 N
E | > 22 N
F | > 30 N




CE
CAT II

ART.NO: 13-3HNFR
60 paia (5 dozen)/Cartone

7	8	9	10	11
XS	S	M	L	XL



PROPIEDADES TÉCNICAS



EN388



3442C

EN407



41XXXX

A: RESISTENCIA A LA ABRASIÓN (1-4)
B: RESISTENCIA AL CORTE (1-5)
C: RESISTENCIA AL DESGARRO (1-4)
D: RESISTENCIA A PERFORACIONES (1-4)
E: ISO RESISTENCIA AL CORTE (A-F)
F: IMPACTO (P=pass)

ISO (A-F)
A | > 2 N
B | ≥ 5 N
C | ≥ 10 N
D | ≥ 15 N
E | ≥ 22 N
F | > 30 N



ART.NO: 13-3HNFR
60 pares (5 docena)/Cartón

CE
CAT II

7 8 9 10 11
XS S M L XL