BORNEO S3

3H037NG

CE UNI EN ISO 20345:2012 S3 SRC ESD

High shoe, MICRO-tech technical fabric thickness 1,8-2,0 mm.
Perspiring and abrasion resistant fabric lining.
Shoe with refracting fabric insert.
Soft, lined and padded tongue.
COMPLETELY METAL FREE SHOE

The shoe satisfies the requirements of slipping resistance on inclined roofs according to **UNI 11583:2015**
TOECAP 200J polymeric **composite non-thermic** according to EN 12568
MIDSOLE flexible antiperforation composite fabric according to EN 12568
SOLE 3HYBRID three-densities polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**
ANTITORSION insert in the sole to assure stability on uneven ground
INSOLE 5000 three-materials extracomfort: perspiring, removable, anatomic, absorbing, ESD and anti-bacterial
The shoes satisfies the requirement according to the norm IEC 61340-4-3:2017 (IEC 61340-5-1:2016) for the electrical resistance **ESD**

Size 36-47 **Shoe weight** Sz 42 **gr. 540**

ALL RIGHTS RESERVED
PATENTED
Pub. no
WO 2018/177684 A1

CERTIFICATIONS

TECHNOLOGIES AND MATERIALS

SECTORS

COMPONENTS AND AUTOMOTIVE
WOOD METAL CARPENTRY
LOGISTICS AND LIGHT INDUSTRY
ESD AREAS
ROOFER

SOLE

3Hybrid is a revolutionary line that thanks to the design of the sole ensures maximum shock absorber and energy return during the entire useful life of the shoe. 3Hybrid belongs to the 3D generation. This shoe is therefore equipped with 3 different layers of sole with relative densities, each specialized to maximize comfort, anti-slip and foot stability. The whole collection is also equipped with an anti-torsion insert to ensure additional support for the foot at every step.

PLUS

ANTI TORSION

ANTI TORSION
The usage of the anti-torsion shank is finalized to give to the shoe extreme stability on every ground. Mostly indicated for the building sector, where the risks caused by uneven and wet grounds are higher, this technology is very useful for people working on ladders (painters, windows' cleaners, bricklayers) as it increases the stability in the centrla part of the plant, the mostly standed area on the ladder. It limits the heel stress and helps plant arch and ankle.

3PU PATENT

3D TRIPLA DENSITA' INIETTATA
3D is a revolutionary certified technology that offers the only shoe with three different layers of polyurethane injected. The most external section, with hard mix, offers the maximum resistance for the surface contact and perfect SRC performances. The middle part, with a softer mix, assures comfort when walking. The higher section, next to the upper, guarantees better stability to the foot. Three densities and the combination of three colors are the special characteristics of this new shoes generation.