

PANAMA S1P

KU083T

CE UNI EN ISO 20345:2012 S1P SRC

Low holed shoe, suede back leather thickness 1,8-2,0 mm.

Highly perspiring and abrasion resistant fabric lining.

Soft, lined and padded tongue.

COMPLETELY METAL FREE SHOE

TOECAP 200J polymeric **composite non-thermic** according to EN 12568

MIDSOLE flexible antiperforation composite fabric according to EN 12568

SOLE KUBE bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92,

to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

INSOLE 4000, removable, anatomic, absorbing, antistatic and perspiring

Size 35-49 Shoe weight Sz 42 gr. 530




CERTIFICATIONS



TECHNOLOGIES AND MATERIALS



SECTORS

 COMPONENTS AND AUTOMOTIVE
LOGISTICS AND LIGHT INDUSTRY

 WOOD METAL CARPENTRY



SOLE



In order to avoid the high number of accidents caused by slipping danger, Giasco realized an excellent anti-slipping product. This sole is called Kube, a young and sporty styled shoe equipped with a special gripping compound and specific cubic dowels with inverted profile in the outsole. With thanks to these special characteristics Kube obtained the maximum certification against slipping: jobs on inclined roofs (UNI 11583:2015).

PLUS

ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS			
SRC			
SRB	HEEL=0.5/0.8	0.45	0.45
SRB	PLATE=0.5/0.8	0.45	0.45
SRB	HEEL=0.5/0.8	0.30	0.30
SRB	PLATE=0.5/0.8	0.30	0.30