

PERU S1P

KU095T

CE UNI EN ISO 20345:2012 S1P SRC ESD

Sandal, suede leather thickness 1,8-2,0 mm.

Highly perspiring and abrasion resistant fabric lining.

Closing with strap.

COMPLETELY METAL FREE SHOE

TOECAP 200J polymeric **composite non-thermic** according to EN 12568

MIDSOLE flexible antiperforation composite fabric according to EN 12568

SOLE KUBE bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92,

to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

INSOLE 5000, three-materials extracomfort: perspiring, removable, anatomic, absorbing, ESD and anti-bacterial

The shoe satisfies the requirement according to the norm IEC 61340-4-3:2017 (IEC 61340-5-1:2016) for the electrical resistance **ESD**

Size 34-47 Shoe weight Sz 42 gr. 550



CERTIFICATIONS



TECHNOLOGIES AND MATERIALS



SECTORS



SOLE



In order to avoid the high number of accidents caused by slipping danger, Giasco realized an excellent anti-slipping product. This sole is called Kube, a young and sporty styled shoe equipped with a special gripping compound and specific cubic dowels with inverted profile in the outsole. With thanks to these special characteristics Kube obtained the maximum certification against slipping: jobs on inclined roofs (UNI 11583:2015).

PLUS

ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS			
SRC			
ANTISLIPPING INDEX			
DATA	HEEL	HEEL	HEEL
Static	0.50	0.40	0.40
Dynamic	0.50	0.40	0.40
DATA	HEEL	HEEL	HEEL
Static	0.50	0.40	0.40
Dynamic	0.50	0.40	0.40