

LIMA S1P

71T95C

CE UNI EN ISO 20345:2012 S1P SRC ESD CLASS 3

Sandal, suede leather thickness 1,8-2,0 mm.
Highly perspiring and abrasion resistant fabric lining.
Closing with strap.

COMPLETELY METAL FREE SHOE

TOECAP 200J polymeric **composite non-thermic** according to EN 12568

MIDSOLE flexible antiperforation composite fabric according to EN 12568

SOLE ERGO SAFE bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

INSOLE 5000, three-materials extracomfort: perspiring, removable, anatomic, absorbing, ESD and anti-bacterial

The shoes satisfies the requirement according to the norm IEC 61340-4-3:2017 (IEC 61340-5-1:2016) for the electrical resistance **ESD**

Size 36-47 Shoe weight Sz 42 gr. 480



CERTIFICATIONS



TECHNOLOGIES AND MATERIALS



SECTORS

-  COMPONENTS AND AUTOMOTIVE
-  WOOD METAL CARPENTRY
- 
-  LOGISTICS AND LIGHT INDUSTRY
-  ESD AREAS

SOLE



Ergo Safe is the safety shoe useful for people who have problems with back and joint pains. It is in fact the only ergonomic shoe in the market, studied to give a solution to these needs and in the same time to assure a complete protection. This is possible thanks to the round sole, that allows a uniform discharge of body weight all along the sole of the foot, giving a good feeling to the back, the knees and to the heels. Ergo is also studied to improve walking, by giving a better blood circulation and a saving of energy at the end of the day.

PLUS

ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS			
SRC			
SRA	HEEL=0.20	0.31	
	PLATE=0.20	0.31	
SMB	HEEL=0.20	0.22	
	PLATE=0.20	0.22	